




Ray Kiskacı Bleam Clamp BL-LJ-Q



Model			BL-L-JQ 1	BL-L-JQ 2	BL-L-JQ 3	BL-L-JQ 5	BL-L-JQ 10
Kapasite Capacity (kg)			1000	2000	3000	5000	10000
Test Yüğü Test Load (kN)			14.71	29.42	44.13	61.29	122.58
Ayarlanabilir Profil Geniřlięi Adjustable Beam Width (mm)			75-230	75-230	80-320	90-320	90-320
Boyutlar Dimensions (mm)	A	max	278	278	356	356	356
	B	max	380	380	500	500	500
		min	183	183	220	220	250
	C		64	76	100	112	120
	đ		4	6	8	10	12
	E		217	217	277	277	285
	F	max	150	150	220	220	230
		min	90	90	145	145	160
	G		26	26	50	47	52
	D		19	21	23	29	39
Net Aęırlık Net Weight (kg)			3.5	4.5	9.5	11	16



BL-L-J-Q

Yatay Sac Kaldırma Horizontal Clamp BL-QP A/B



BL-QP-B

Model			BL-QP 0.75 A	BL-QP 1.5 A	BL-QP 2.5 A	BL-QP 0.75 B	BL-QP 1.5 B	BL-QP 2.5 B
Kapasite Capacity (kg)	Single		750	1500	2500	750	1500	2500
	Double		1500	3000	5000	1500	3000	5000
Test Yüğü Test Load (kN)	Single		11.04	22.07	36.79	11.04	22.07	36.79
	Double		22.07	44.13	73.58	22.07	44.13	73.58
Max.Çene Açıklığı Max.Jaw Opening (mm)			50	50	60	25	30	40
Boyutlar Dimensions (mm)	A		0-52	0-52	0-62	0-27	0-32	0-52
	B		127	220	260	125	157	231
	C		100	110	130	50	65	90
	Dmax		218	270	315	175	204	310
	E		đ30	đ36	đ40	đ25	đ30	đ40
Net Aęırlık Net Weight (kg)	Single		4.3	7.7	14.1	2.4	3.9	13.4
	Double		8.6	15.4	28.2	4.8	7.8	26.8